



| Capacity | A'   | A ABORD | A INDEPEN. | A CITRUS | B    | C    | Weight (kg) |
|----------|------|---------|------------|----------|------|------|-------------|
| 1.000 L  | 2010 | 2440    | 2530       | 2680     | 1145 | 1460 | 545         |
| 1.500 L  | 2360 | 2790    | 2880       | 3030     | 1330 | 1500 | 595         |
| 2.000 L  | 2490 | 2920    | 3010       | 3160     | 1410 | 1540 | 660         |

## Technical Features

**TANK** Made of high-density reinforced polyethylene; our tanks exist in 1000, 1500 and 2000 litres versions. They include integrated detachable clean water tank, washing device tank and wide filling hole with filter and hermetic lid.

**FRAME** Made of steel in a "U" shape with detachable bumper on the rear part, footboard, towing drawbar and parking foot.

**FAN** Made of steel, hot dipped galvanized, the fans main features are the following:  
**ABORD** model: 810 mm fan with 20 polypropylene blades. 14 brass double outlet anti-drip nozzle. Transmission by reinforced PTO shaft with security protection and a 2 speed / neutral oil bath gearbox  
**INDEPENDENT** model: 840 or 940 mm. fan with inner stator with 10 blades and 10 aluminium adjustable blades (from 15 to 45°). 14 brass double outlet anti-drip nozzle. Transmission by reinforced PTO shaft with security protection and a 2 speed / neutral oil bath gearbox. Centrifugal clutch.  
**CITRUS** model: 840 or 940 mm. fan with inner stator with 10 blades and 10 aluminium adjustable blades (from 15 to 45°) and 3 air outlets. 26 brass double outlet anti-drip nozzle. Transmission by reinforced PTO shaft with security protection and a 2 speed / neutral oil bath gearbox. Centrifugal clutch.

| Mist blower model                       | Blade angle | Gear | Air volume (m <sup>3</sup> /h) | Outlet speed (m/s) |
|-----------------------------------------|-------------|------|--------------------------------|--------------------|
| <b>ABORD</b><br><b>810 mm fan</b>       | standard    | high | 50 000                         | 25                 |
|                                         |             | low  | 40 000                         | 20                 |
| <b>INDEPENDENT</b><br><b>840 mm fan</b> | 35 °        | high | 58 000                         | 32                 |
|                                         |             | low  | 46 000                         | 28                 |
| <b>INDEPENDENT</b><br><b>940 mm fan</b> | 35 °        | high | 60 000                         | 35                 |
|                                         |             | low  | 52 000                         | 30                 |

**PUMP** Italian COMET pump.

**STIRRER** Two high-pressure easy-check hydraulic "TURBOMAX" stirrers.

**CONTROLS** COMET **GRH** manual control unit with constant pressure regulation valve and pressure gauge. Total and partial shut off lever (2 outlets).

**FILTERS** Three filtration levels: filter in the filling hole, high-density aspiration filter (close to the pump) including security valve that allows inspection even when tank is full, 2 brass in-line filters on the front part of the machine.

**asesores y técnicas agrícolas, S.a.**

Avda de las Americas, s/n - Pol. Ind. Oeste - Parc. 17/3 - 30820 Alcantarilla (MU) - España.  
Tél. +34 968 89 11 11 - Fax. +34 968 80 85 13 - Email: [atas@atasacomet.com](mailto:atas@atasacomet.com)



# atasa

MAQUINARIA PARA LA PROTECCIÓN DE CULTIVOS

Sprayers for crop protection



**atasa polyethylene mistblowers**